

## Coaxial 30W 0° 2-Way Power Divider 4~18GHz



### Features

- High power handling up to 30W
- Wide band operation
- High isolation within operational band
- Low Insertion Loss
- Stable performance over temperature

### Typical Applications

- Aerospace and Military Applications
- Wireless Infrastructure
- Test and Measurement

Electrical Specifications,  $T_A=25^\circ\text{C}$

Parameters		Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range		4		8	8		18	GHz
Nominal Splitter Loss			3			3		dB
Insertion Loss			0.3	0.4		0.5	0.7	dB
Isolation		18	20		18	20		dB
Input VSWR			1.4	1.5		1.4	1.5	: 1
Output VSWR			1.4	1.5		1.4	1.5	: 1
Amplitude Imbalance			0.1	0.2		0.1	0.2	dB
Phase Imbalance			2	3		3	4	deg
Power Rating	Forward Power	30						W
	Reverse Power	1						W
	Peak Power	300 (10% Duty Cycle, 1 us Pulse Width)						W
Impedance		50						Ohms
Weight		1.0 Max.						ounces
Input / Output Connectors		SMA-Female						
Material		Aluminum						
Finish		Blue Paint						


Coaxial 30W 0° 2-Way Power Divider 4~18GHz

**Environmental Specifications and Test Standards**


Parameter	Description
Operational Temperature	-40°C~+85°C (Case Temperature)
Storage Temperature	-50°C~+105°C
Thermal Shock	-40°C → +85°C (5 Cycles / 10 hours)
Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +85°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

## Typical Performance Plots


### Loss & Amplitude Imbalance




### Input VSWR




### Output VSWR



### Isolation



### Phase Imbalance




**Outline Drawing:**

All Dimensions in mm [inches]

Outline Tolerances  $\pm 0.5$  [0.02]

Mounting Hole Tolerances  $\pm 0.2$  [0.008]



**Coaxial 30W 0° 2-Way Power Divider 4~18GHz**

**Important Notice**

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.