# SPA-2-6-50 Solid State Power Amplifier

(2GHz - 6GHz, 50W)

#### **Key Features**

- Multi-octave broadband performance
- High output power
- Wide dynamic range
- High-efficiency GaN technology
- Low power consumption
- Low spurious signal
- Forward/reverse power monitoring
- Extremely load-resistant
- Over voltage, over temperature, over current protection
- Optional overdrive protection
- CE, RoHS certification



#### Overview

Saluki SPA-2-6-50 is a solid-state RF power amplifier with an output frequency of 2GHz to 6GHz and an output power of 50W. Its design is based on the most advanced GaN technology in the industry, and its power output is efficient and reliable. It is mainly used for testing and measuring instruments, Communication or interference, aviation control and other fields. The product has functions such as temperature and current detection, alarm protection and so on.

### **Technical Specifications**

SPA-2-6-50				
Frequency Range	2GHz - 6GHz	Input Power	0dBm (max.)	
Output Power	50W (min.)	Harmonic	-15dBc @40W	
P1dB Output Power	40W (min.)	Spurious	-60dBc (max.)	
Gain	47dB (min.)	Input VSWR	1.5:1 (max.)	
Gain Flatness	± 3dB (max.)	VSWR Protection	5:1	
Adjustable Gain	20dB (max.)	Impedance	50 ohm	




# SPA-2-6-50 Solid State Power Amplifier

(2GHz - 6GHz, 50W)

Input Port	Type- N (female)	Output Port	Type- N (female)
Monitoring Port	Type- N (female)	Cooling Type	Air cooling
Communication	LAN	Dawer Summly	AC 220V±10%,
Interface	LAN Power Supply		50/60Hz
Dimension	19", 3U	Operating Temperature	0 - 50℃

#### **Outline Structure**



## **Options**

Module No.	Item
001	Overdrive protection
002	GPIB interface

Note: Information will conduct the necessary updates, the contents of this document are subject to change without notice.

